

Delivery Range Serial Cabinets FXA to IP55. Standard Delivery Programme

Standing cabinets, extremely resilient, up to IP55

Material:	Stainless steel 1.4301, AISI 304* Stainless steel 1.4404, AISI 316L, (V4A)* Stainless steel 1.4571, AISI 316Ti, (V4A)*
Material thickness:	Body 2 mm, fully welded
Surface:	polished, grain size 240
Protection class:	Single cabinets IP55 Double-door with fixed middle bridge IP55 Double-door with removable middle bridge and sealing set IP55 Double-door without middle bridge IP54
Hinges:	Stainless steel, 180° hinge Door stop right*, door stop left*, double-door*
Closing:	Rod lock
Seal:	Neoprene seal 6x20mm* or silicone seal 6x20mm*
Dimensions:	See table. Other sizes available. *please indicate in your order



Designation	Size in Height	(mm) x	Width	x	Depth	Mat.thickness MP (mm)	Closure	Number Doors
FXA 16064	1600	x	600	x	400	3	STS	1
FXA 16084	1600	x	800	x	400	3	STS	1
FXA 18064	1800	x	600	x	400	3	STS	1
FXA 18065	1800	x	600	x	500	3	STS	1
FXA 18066	1800	x	600	x	600	3	STS	1
FXA 18084	1800	x	800	x	400	3	STS	1
FXA 18085	1800	x	800	x	500	3	STS	1
FXA 18086	1800	x	800	x	600	3	STS	1
FXA 18104	1800	x	1000	x	400	3	STS	1
FXA 18105	1800	x	1000	x	500	3	STS	1
FXA 18106	1800	x	1000	x	600	3	STS	1
FXA 18124	1800	x	1200	x	400	3	STS	2
FXA 18125	1800	x	1200	x	500	3	STS	2
FXA 18126	1800	x	1200	x	600	3	STS	2
FXA 20064	2000	x	600	x	400	3	STS	1
FXA 20065	2000	x	600	x	500	3	STS	1
FXA 20066	2000	x	600	x	600	3	STS	1
FXA 20084	2000	x	800	x	400	3	STS	1
FXA 20085	2000	x	800	x	500	3	STS	1
FXA 20086	2000	x	800	x	600	3	STS	1
FXA 20104	2000	x	1000	x	400	3	STS	1
FXA 20105	2000	x	1000	x	500	3	STS	1
FXA 20106	2000	x	1000	x	600	3	STS	1
FXA 20124	2000	x	1200	x	400	3	STS	2
FXA 20125	2000	x	1200	x	500	3	STS	2
FXA 20126	2000	x	1200	x	600	3	STS	2

STS= Bar lock

Other housings in standard equipment can be calculated and ordered online as well now: www.gehaeusekalkulator.de